

N-495 Computerised Lumber-Cervical-Ankle Traction Unit

PROTEUS



Table A Size : L 7.5 Ft. x W 2.25 Ft. x H 2.25 Ft.



Table B Size : L 7.5 Ft. x W 2.0 Ft. x H 2.25 Ft.

FEATURES

- ☐ Accurate & sturdy traction unit
- ☐ Noiseless, reliable, durable heavy-duty Motor
- ☐ Patient-operated Safety Switch
- ☐ Highly user - friendly Control Panel
- ☐ Easy to Operate design.

Input Supply : 230 V Ac, 50 Hz

Size : 13 X 10.5 X 12

Weight : 11 Kg Approx

ACCESSORIES:

- ☐ One cervical collar
- ☐ One cervical spreader bar
- ☐ One wall mounting clamp for cervical traction
- ☐ One pair lumber, ankle and chest belt

TECHNICAL SPECIFICATIONS:

MODE	: Intermittent / Static
HOLD TIME	: 20, 30, 40, 50, 60, 70, 80 Sec.
REST TIME	: 1 to 20 Sec.
TIMER	: 1 to 60 min.
MOUNTING	: Traction Table Mount, Wall Mount
TRACTION FORCE	: 5, 7, 8, 9, 10, 15, 20, 25, 30, 35, 40, 45 kgs.
BUZZER	: Audio buzzer at the end of treatment time.
CLASS/DEGREE	
OF PROTECTION	: 1/ Type BF
SAFETY STANDARD	: IEC 60601-1